



RANGE NAME: VULCAN

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.



Ice 52



Mistral 24



Mint 35



Beige 14



Stone 36



Marine 39



Malachite 23



Lemon 34



Grey 8



Purple 38



Teal 27



Mustard 30



Slate 11



Violet 19



Petrol 16



Taupe 32



Black 1

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.

			
Skye 57	Dusk 40	Wasabi 49	Salt 55
			
Airforce 51	Peacock 59	Mamba 47	Blonde 21
			
Bahama 26	Dive 3012	Pesto 46	Fennel 60
			
Cobalt 50	Antarctic 3013	Lime 9	Tendrill 3006
			
Hyacinth 2	Atlantis 3011	Sage 29	Eucalyptus 3009
			
Sapphire 58	Midnight 6	New England 3008	Woodland 4

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.



Solar 3005



Sunset 48



Sable 22




Sand 53




Mexican 3007



Orange 33



Rose 37




Tutu 3003



Caramel 61




Naartjie 44



Rust 5




Purity 3002



Melon 54



Jaffa 43




Brick 12




Captivate 3004



Clay 3001



Soviet 45




Roux 20



Grape 56



Post 3010



Fire 42



Garnet 3



DK. Claret 31

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.



RANGE NAME: ARAGON

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.

APPLICATION: UPHOLSTERY & SCREENING
COMPOSITION: 100%
PES WIDTH: 142cm
MASS: 310 gm/1m
PATTERN REPEAT: PLAIN
COMPLIES WITH: SABS 1324 OFFICE PARTITIONS SPECIFICATION.

COLOUR FASTNESS:

		STD	ARAGON
ABRASION RESISTANCE:		25,000 RUBS	+25,000 RUBS
TO LIGHT:		4	4
TO RUBBING:		4	4
PILLING:		4	4
SEAM SLIPPAGE:	WARP	180N	180N
TENSILE STRENGTH:	WARP	400N	400N


PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.



Aragon Whirl



Aragon Toffee



Aragon Valencia



Aragon Tari



Aragon Tar



Aragon Sandlewood



Aragon Iceland



Aragon Pandora



Aragon Moss



Aragon Fungus



Aragon Goth



Aragon Gargoyle



Aragon Bear



Aragon Floss



Aragon Delft




Aragon Crop



Aragon Alter



Aragon Blood



Aragon Castle

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.



RANGE NAME: OMNIA

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.

APPLICATION: UPHOLSTERY & SCREENING
COMPOSITION: 100% PES
PES WIDTH: 142cm
MASS: 346 gm/1m
PATTERN REPEAT: PLAIN
COMPLIES WITH: SABS 1324 OFFICE PARTITIONS SPECIFICATION.

COLOUR FASTNESS:

		STD	OMNIA
ABRASION RESISTANCE		25,000 RUBS	+45,000 RUBS
TO LIGHT:		5	5
TO RUBBING:		4-5	4-5
TO DRY CLEANING:		4	4
TO PERSPIRATION:		4	4
PILLING:		4-5	4-5
SEAM SLIPPAGE:	WARP	180N	180N
	WEFT	180N	180N
TENSILE STRENGTH:	WARP	400N	1500N
	WEFT	400N	1055N

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.



692319

692318

692317

692313

692316



692315

692312

692311

692307

692308



692306

692305

692303

692302

692301



692320

692309

692304

692310

692314

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.



RANGE NAME: SUPALETHA BONDED LEATHER

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.

APPLICATION: UPHOLSTERY & SCREENING
PES WIDTH: 140cm
PATTERN REPEAT: PLAIN
COMPLIES WITH: ATS Test and SABS 2532/L1/IL75

COLOUR FASTNESS:

TEST	ATS TEST METHOD	SPECIFICATION		TEST RESULTS	
		WARP	WEFT	WARP	WEFT
ABRASION RESISTANCE	EN ISO 12947-2:1998	>250 000 Revs		770 N	700 N
TENSILE STRENGTH	EN ISO 13934-2:1999	720 N/in	650 N/in	70 N	80 N
TEAR STRENGTH	EN ISO 1397-3:2000	35 N	40 N	31 N	49 N
PEALING STRENGTH	EN ISO 2411:2000	30 N	25 N	447 N	408 N
SEAM STRENGTH	EN ISO 13936-2:2004	≥ 200 N		N	N
COLOUR FASTNESS TO RUBBING	EN ISO 105-X12:2002	5		Dry:	5
		5		Wet:	5
COLOUR FASTNESS TO LIGHT	EN ISO 105-B02	≥ 4		Passed (6)	
FLEXING RESISTEANCE	EN ISO 32 100	100 000 Revs		No Cracks/No Delamination	
BALLY TEST AFTER HYDROYSIS	EN ISO 32100	15 000 Revs		No Cracks/No Delamination	

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.



SL28 SL24 SL103 SL12 SL13 SL104



SL2 SL10 SL11 SL29 SL57 SL61



SL101 SL102 SL109

PLEASE NOTE: Due to monitor differences, actual colours may vary from what appears online.