

ZHEJIANG RUNDA KEHONG FURNITURE CO., LTD

BUILDING 1, FAN TAN INDUSTRIAL ZONE, LING FENG STREET, ANJI COUNTY, ZHEJIANG PROVINCE, CHINA


The following sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion. Results apply to the sample as received.

Sample Description	OFFICE CHAIR
Style / Item No.	POLAR
Manufacturer Name	ZHEJIANG RUNDA KEHONG FURNITURE CO., LTD
Country of Origin	CHINA
Country of Destination	USA
Sample Receiving Date	MAY 29, 2020
Sample Re-submitted Date	JUN 30, 2020
Test Performing Date	MAY 29, 2020 TO JUL 14, 2020

Test Result Summary

Test(s) Requested	Result(s)
ANSI/BIFMA X5.1-2017	PASS
Remark:	
1. This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included. 2. For further details, please refer to the following page(s).	

Signed for and on behalf of
SGS-CSTC Co., Ltd. Anji Branch




David Fan
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Conducted: ANSI/BIFMA X5.1 -2017 General-Purpose office chairs -Tests

Test Result:

Test Item	Test Principle & Requirement	Test Result
Backrest Strength Test - Static - Type I and II (Functional Load) (Clause 5)	There shall be no loss of serviceability when a force of 667N (150lbf.) is applied 70°± 10° to the back at 406mm (16in.) above the seat for 1 minute.	PASS
Backrest Strength Test - Static - Type I and II (Proof Load) (Clause 5)	There shall be no sudden and major change in the structural integrity (loss of serviceability is acceptable) when a force of 1001N (225lbf.) is applied 70°± 10° to the back at 406mm (16in.) above the seat for 1 minute.	PASS
Backrest Strength Test - Static - Type III (Functional Load) (Clause 6)	There shall be no loss of serviceability when a force of 667N (150lbf.) is applied 90°± 10° to the back at 406mm (16in.) above the seat for 1 minute.	PASS
Backrest Strength Test - Static - Type III (Proof Load) (Clause 6)	There shall be no sudden and major change in the structural integrity (loss of serviceability is acceptable) when a force of 1001N (225lbf.) is applied 90°± 10° to the back at 406mm (16in.) above the seat for 1 minute.	PASS
Drop Test–Dynamic (Functional Load) (Clause 7)	There shall be no loss of serviceability when a 102kg (225lb.) weight free falls from 152mm (6in.) height to the center of the seat one time (for the seat height is adjustable, test one time in its highest position then one time in its lowest position).	PASS
Drop Test Dynamic (Proof Load) (Clause 7)	There shall be no sudden and major change in the structural integrity (loss of serviceability is acceptable) when a 136kg (300lb.) weight free falls from 152mm(6in.) height to the center of the seat one time (for the seat height is adjustable, test one time in its highest position then one time in its lowest position).	PASS
Swivel Test – Cyclic (Clause 8)	There shall be no loss of serviceability after 120,000 cycles of rotation with a 122kg (270lb.) load on the seat (for the seat height is adjustable, test 60,000 cycles in its highest position then 60,000 cycles in its lowest position).	PASS
Tilt Mechanism Test – Cyclic –Type I & II (Clause 9)	There shall be no loss of serviceability after moving the mechanism between the front and back stops for 300,000 cycles with a 109kg (240lb.) load on the seat.	PASS
Seating Durability Tests – Cyclic (Impact Test) (Clause 10.3)	There shall be no loss of serviceability after a 57kg (125lbs.) weight free falls onto the seat from 36mm (1.4in.) height for 100,000 cycles.	PASS
Seating Durability Tests – Cyclic (Front Corner Load – Ease Test – Cyclic – Off-center) (Clause 10.4)	There shall be no loss of serviceability after loading two seat front corner with 890N (200lbf.) for 20,000 cycles respectively.	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Technical Services Co., Ltd. | No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Item	Test Principle & Requirement	Test Result
Rear Stability Test for Type III Chairs (Clause 11.3.1)	The chair shall not tip over when applying a horizontal force to 6mm (0.25 in.) from the top of disk with 6 disks on the chair against backrest support fixture. Determine the horizontal force: H ≥ 710mm, F = 93N; H < 710 mm, F = 0.1964 (1195-H) where: H is the seat height measured at the front of the bottom of the lowest disk when all disks are in the chair, in mm	PASS
Rear Stability Test for Type I and II Chairs (Clause 11.3.2)	The chair shall not tip over when applying 13 disks on the seat against backrest support fixture.	PASS
Front Stability (Clause 11.4)	The chair shall not tip over when applying a horizontal outward force of 20N (4.5lbf.) from the seat with a vertical load of 61kg (135lbf.) at a point 60mm (2.4in.) from the front center edge of the load bearing surface of the seat.	PASS
Arm Strength Test – Vertical – Static (Functional Load) (Clause 12)	There shall be no loss of serviceability when a force of 750N (169lbf.) is applied vertically to the armrest for 1 minute.	PASS
Arm Strength Test – Vertical – Static (Proof Load) (Clause 12)	There shall be no sudden and major change in the structural integrity (loss of serviceability is acceptable) when a force of 1125N (253lbf.) is applied vertically to the armrest for 15s.	PASS
Arm Strength Test – Horizontal – Static (Functional Load) (Clause 13)	There shall be no loss of serviceability when a force of 445N (100lbf.) is applied horizontally outward to the armrest for 1 min.	PASS
Arm Strength Test – Horizontal – Static (Proof Load) (Clause 13)	There shall be no sudden and major change in the structural integrity (loss of serviceability is acceptable) when a force of 667N (150lbf.) is applied horizontally outward to the armrest for 15s.	PASS
Back Durability Test – Cyclic – Type I (Clause 14)	There shall be no loss of serviceability when a force of 445N (100lbf.) is applied 90° ± 10° to the back at 406mm (16in.) above the seat for 120,000 cycles with 109kg (240lbs.) weight on the seat.	PASS
Back Durability Test – Cyclic – Type II & III (Clause 15)	There shall be no loss of serviceability when a force of 334N (75lbf.) is applied 90° ± 10° to the back at 406mm(16in.) above the seat for 120,000 cycles with 109kg (240lbs.) weight on the seat.	PASS
Caster/Chair Base Durability Test for Pedestal Base Chairs (Clause 16.1)	There shall be no loss of serviceability after cycling a travel of (762±50)mm ((30±2)in.) for 2,000 cycles over a surface with obstacles and then 98,000 cycles over a surface without obstacles with a 122kg (270lb.) load on seat. The caster should not separate under 22N (5lbs.) pulling force.	PASS
Caster/Chair Frame Durability Test for Non-pedestal Chairs with Casters (Clause 16.2)	There shall be no loss of serviceability after cycling a travel of (762±50)mm ((30±2)in.) for 2,000 cycles over a surface with obstacles and then 98,000 cycles over a surface without obstacles with a 122kg (270lb.) load on seat. The caster should not separate under 22N (5lbs.) pulling force.	NA



Test Item	Test Principle & Requirement	Test Result
Leg Strength Test (Front Load Test) (Functional Load) (Clause 17.3)	There shall be no loss of serviceability when a horizontal rearward force of 334N (75lbf.) is applied inward to each front leg individually for 1 minute.	NA
Leg Strength Test (Front Load Test) (Proof Load) (Clause 17.3)	There shall be no sudden and major change in the structural integrity (loss of serviceability is acceptable) when a horizontal rearward force of 503N (113lbf.) is applied inward to each front leg individually for 1 minute.	NA
Leg Strength Test (Side Load Test) (Functional Load) (Clause 17.4)	There shall be no loss of serviceability when a horizontal sideward force of 334N (75lbf.) is applied inward to each front and rear leg individually for 1 minute.	NA
Leg Strength Test (Side Load Test) (Proof Load) (Clause 17.4)	There shall be no sudden and major change in the structural integrity (loss of serviceability is acceptable) when a horizontal sideward force of 503N (113lbf.) is applied inward to each front and rear leg individually for 1 minute.	NA
Footrest Static Load Test – Vertical (Functional Load) (Clause 18)	There shall be no loss of serviceability or sudden loss of footrest height when applying two vertical forces of 445N (100lbf.) opposite to footrest for 1 minute firstly, then increase one force to 890N (200lbf.) for 1 minute.	NA
Footrest Static Load Test – Vertical (Proof Load) (Clause 18)	There shall be no sudden and major change in the structural integrity (loss of serviceability is acceptable) when applying a vertical force of 1334N (300lbf.) to footrest for 1 minute.	NA
Footrest Durability Test (Clause 19)	There shall be no loss of serviceability (adjustable footrests that move more than 25mm (1in.) in the first 500 cycles shall be considered to have lost their serviceability) after a force of 890N (200lbf.) is applied vertically on the footrest for 50,000 cycles.	NA
Arm Durability Test- Cyclic (Clause 20)	There shall be no loss of serviceability when a force of 400N (90lbf.) is applied simultaneously to each arm at a 10° ±1° angle for 60,000cycles.	PASS
Out Stop Tests for Chairs with Manually Adjustable Seat Depth (Clause 21)	There shall be no loss of serviceability after releasing the seat for 25 cycles from its most rearward position to impact out stops under a 25kg (55lb.) weight attached downward with a 74kg (163lb.) mass loaded on seat.	PASS
Tablet Arm Chair Static Load Test (Clause 22)	There shall be no sudden and major change after applying a load of 68kg (150lb.) at the surface of tablet arm for 1 minute.	NA
Tablet Arm Chair Load Ease Test - Cyclic (Clause 23)	There shall be no loss of serviceability after applying a force of 25kg (55lb.) to the surface of tablet arm for 100,000 cycles.	NA
Structural Durability Test – Cyclic (Clause 24)	There shall be no loss of serviceability after applying a force of 334 N (75 lbf.) to the unit frame midway between front and rear of the seat at the height of the midpoint of the seat frame structure for 25000 cycles with a 109 kg (240 lb.) on the center of the seat. One cycle shall consist of one outward force application and removal and one inward force application and removal.	NA



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Remark:

1. Type of chair:

Type I – tilt chair: A chair with a seat and backrest that tilt (either in unison or in synchronization) with a counterbalancing force. Chairs of this type are typically referred to as synchro-tilt, center-tilt, knee-tilt, etc.

Type III–fixed seat angle, fixed backrest: A chair that provides a fixed seat angle with a fixed backrest. This may include chairs with legs, including sled base chairs.

2. NA=Not applicable

Photo Appendix



Sample as received - View 1



Sample as received - View 2



Sample as received - View 3



Sample as received - View 4

SGS authenticate the photo on original report only

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com